



Cheetah

NIGHT VISION 3-IN-1

Day and night performance

HIKMICRO Cheetah Digital Night Vision Monocular can be easily transformed into a scope and performs well under any lighting condition. Its advanced 2560 x 1440 HD sensor and 1920 x 1080 OLED display are capable of capturing every object in great detail and with rich clarity.

T T	MODEL	RANGE	FOV	MAG	SENSOR	RRP
	C32FS KIT	400m	8.1° × 6.1°	2.7x-21.6	2560×1440.850nm	\$1,099
뽀	C32FSL KIT	40011	0.1 × 0.1	Z./X-Z1.0	2360*1440,6301111	\$1,499
U						

*fixed at base magnification in clip-on mode ** Ballistic Calculator features on all LRF Models





Compact yet powerful

High thermal sensitivity, perfect detail recognition. Every detail matters when identifying targets. Less than 20 mK NETD helps identify small details of objects from their background easily and clearly even in the hardest weather and low- light conditions.

	MODEL	RANGE	FOV	MAG	SENSOR	RRP
HER	PQ50L 2.0	2600m	8.8° × 7°	2.6 - 20.8	640 × 512, 12 µm	\$6,299
	PQ35L 2.0	1800m	12.5° × 10°	1.77 - 14.16	NETD < 20mK	\$5,299
Z N	PH50L 2.0	2600m	5.3°×4°	4.22 - 33.76	384 × 288, 12 µm	\$4,799
PA	PH35L 2.0	1800m	7.5° × 5°	2.96 - 23.68	NETD < 20mK	\$4,299

** Ballistic Calculator features on all LRF Models

EXPLORER

SMARTPHONE THERMAL CAMERA

Ultimate in Portability

Thermal Camera for Android Smartphone, the E20PLUS is designed for consumer applications for outdoor activities such as bird watching, hiking, camping, sports & concerts.

MODEL	RANGE FOV	MAG	SENSOR	RRP
E20	970m 18.1° × 13.6°	2x	256 × 192 NETD < 50mK	\$599



TRAIL CAMERA Powerful & Robust

** Includes BONUS 32gb SD Card

The HIKMICRO M15 wildlife camera is a powerful and robust 4C-equipped camera ideal for wildlife observation and is an extremely useful device for hunting and a variety of other outdoor activities.

MODEL	RANGE	FEATURE	SENSOR	RRP	
M15	25m Identification Range	.5 Second Trigger Speed	1080P 940nm	\$349	
SP5000	000 SOLAR PANEL - Powerbank				



Enhanced Resolution

The Habrok Pro & 4K models combine thermal and digital optical channels, enhancing outdoor experiences. Compact like traditional binoculars but packed with advanced tech. Detect in thermal, view in optical, and record to built-in memory.

	MODEL	RANGE	FOV	MAG	SENSOR	RRP
	HX60L	3100m/400m	7.3°×4.1° 14.6°×8.8°	D 5.5-22 T 2.6- 26	1280×1024, 12µm NETD < 18mK	\$9,999
	HQ50L	2600m/400m	7.3°×4.1° 8.8°×5.3°	D 5.5-22 T 4.3 - 25.8	640×512, 12µm NETD < 15mK	\$6,499
BROK 0 & 4K	HQ35L	1800m / 400m	13.9°×7.8 12.5°×10.1°	D 2.9 - 23.2 T 3-24	640×512, 12 µm NETD < 20mK	\$5,599
HAB	HH35L	18001117 400111	13.9°×7.8° 7.5°×5.7°	D 2.9 - 23.2 T 4-32	384×288, 12 µm NETD < 20mK	\$4,349
	HE25L	1200m/400m	6.9°×4.1° 7°×5.3°	D 5.5-22 T 4.3 - 17.2	256×192, 12µm NETD < 35mK	\$2,499

All Habrok range also available in a 940nm



All-in-one Solution

In combination with thermal camera, digital day & night camera, and laser rangefinder, the ultimate innovative RAPTOR series binocular provides unprecedented observation capability in thermal or true living color,up close or from a distance, during day or night in all weather conditions.

	MODEL	RANGE	FOV	MAG	SENSOR	RRP
RAPTOR	RQ50LN		8.8° × 7.0° 3.4-54.4, ×16	640 × 512, 12 µm	\$7,599	
	RQ50L	2600m	0.0 × 7.0	3.4-34.4, ^10	NETD < 20mK	\$7,599
	RH50LN		F.7°. / 0°	3°×40° 5.7-91.2.×16	NETD < 20ml/	\$5,899
	RH50L		5.3°×4.0°	5.7-91.2, ×10		\$5,899

Au Office number 0488 647 667

Au Office Email australia@huntsmanoptics.com























THE ULTIMATE IN
THERMAL AND NIGHT VISION SOLUTIONS



Lynx 2.0 &



Lightweight & Compact

THERMAL MONOCULAR

Compact and light with a very comfortable and robust feel to it, the LYNX Monocular has the ultimate thermal performance housed in a small package. With advanced engineering, the refresh rate is smooth and fast - eliminating the need for recalibration as you scan your hunting zone.

	MODEL	RANGE	FOV	MAG	SENSOR	RRP
YNX 2.0	LH35 2.0	1800m	7.5°×5.7°	3.3x-26.4		\$2,299
	LH25 2.0	1200m	10.5° × 7.9°	2.4-19.2		\$2,099
	LH19 2.0	900m	13.7°× 10.3°	1.8-14.4	384 × 288, 12µm NETD < 20mK	\$1,899
	LH15 2.0	750m	17.5° × 13.1°	1.4-11.2	11213 1201111	\$1,699
S	LE15 S	750m	11.7°×8.8°	2.2-17.6	256 × 192, 12µm NETD < 35mK	\$999
ž	LE10 S	500m	18.0°×13.6°	1.5-12.0		\$699
_	LC06 S	250m	24.7°×18.7°	1.0- 4.0		\$579





Industry Leading Thermal Performance

The Falcon thermal monocular combines an advanced NETD<15 mK sensor with an F0.9 lens, ensuring exceptional imaging even in tough weather. The Falcon boasts a durable design, intuitive controls, and a 5-hour battery. Unique "Image Pro mode" enhances detail, supported by 64GB internal storage.

MODEL	RANGE	FOV	MAG	SENSOR	RRP
FQ50L 2.0	2600m	8.8° × 7.0°	26 20 0		\$4,999
FQ50 2.0	2600111	8.8 × 7.0	2.6-20.8	640 × 512, 12 μm NETD < 15mK	\$4,299
FQ35 2.0	1800m	12.5°×10°	1.8×-14.4		\$3,699
FH35	1800m	7.5° × 5.7°	3.0×-24.0	384 × 288, 12 µm NETD < 20mK	\$2,599



Remarkable image quality

Condor

THERMAL MONOCULAR

This compact spotter is equipped with a powerful, high-sensitivity NETD<15 mK thermal detector, which captures exceptionally fine detail. The result is a vivid, layered image, which doesn't just make it easy to spot and identify target quarry but also gives a very clear view of the surrounding landscape.

	MODEL	RANGE	FOV	MAG	SENSOR	RRP
œ	CQ50L 2.0	2600m	8.7° × 7°	3 - 24	640 ×5 12, 12 µm	\$4,699
0	CQ35L 2.0	1800m	12.5° × 10.0°	2 - 16	NETD < 15mK	\$4,099
NOS	CH35L	1800m	7.5° × 5.6°	3.5 - 28	384 × 288, 12 µm NETD < 20mK	\$2,999
ŏ	CH25L	1200m	10.5° × 7.9°	2.5 - 20		\$2,699



THERMAL TUBE SCOPE



HIKMICRO

Traditional tube with powerful performance.

The Stellar 3.0 Thermal Scopes feature high-resolution detectors (up to 1280 × 1024), 2560 × 2560 OLED displays, and NETD<15 mK sensitivity. With up to 3100 m detection range, built-in laser rangefinder, ballistic calculation, and 10-hour battery life, they offer precision and reliability for field and forest hunting.

	MODEL	RANGE	FOV	MAG	SENSOR	RRP
LLAR 3.0	SX60L 3.0	3100m	14.6° × 11.7°	2.5-28.5	1280 × 1024, 12 µm NETD < 18mK	\$9,999
	SQ50L 3.0	2600m	8.8° × 7.0°	3.6-26.6	640 × 512, 12 µm	\$6,499
	SQ35L 3.0	1800m	12.5°×10°	2.5-24.5	NETD < 15mK	\$5,799
	SH50L 3.0	2600m	5.3° × 4°	6-24		\$4,799
STE	SH35L 3.0	1800m	7.5° × 5.7°	4.2-24.2	384 × 288, 12 µm NETD < 15mK	\$3,999
	SH35 3.0					\$3,499



Born for Low Light

The HikMicro Alpex with advanced sensor technology and image processing to deliver a detailed, full colour image throughout the day automatically adjusting to twilight and continuing to display an amazing full colour image up until total darkness.

	MODEL	RANGE	FOV	MAG	CMOS RESOLUTION	RRP
Ϋ́	A50EL	1000m				\$1,499
X	A50EL KIT		8.8° × 5.0°	3.5 - 28	3840 × 2160	\$1,849 \$1,249
H H	A50E		0.0 ^ 5.0	3,3 - 28	3840 ^ 2100	
₹	A50E KIT					\$1,599

* Ballistic Calculator features on all LRF Models



Low Light Clarity

The 1440×1080 HD CMOS sensor gives a ground-breaking image in both day and night. Making the HikMicro Alpex the obvious winner when it comes to LOW-LIGHT HUNTING.

	MODEL	RANGE	FOV	MAG	CMOS RESOLUTION	RRP
EX	A50T-S	600m	7.7° ×5.8°	3.5 - 14	1920 × 1080	\$869
ALF	A50T-S KIT	000111	7.7 ~5.0	3.5 - 14	1920 ^ 1000	\$1,199

www.huntsmanoptics.com







Thunder 2.0

THERMAL SCOPE

Impressive Detail Recognition

With an extremely high thermal sensitivity (NETD<20mK) detector combining a powerful thermal camera of up to 640x512 @12µm @ F1.0, it ensures informative images and an enhanced identification capability even under the slightest temperature differences.

RANGE	FOV	MAG	SENSOR	RRP
2600m	8.7° × 7°	2.6 - 20.8	640 × 512, 12 µm	\$5,999
1800m	12.5° × 10°	1.8 - 14.6	NETD < 20mK	\$4,999
	7.5°× 5.7°	3 - 24	384 × 288, 12 μm NETD < 20mK	\$3,999
1200m	10.5° ×7.9°	2.2 - 17.6		\$3,399
	7.0° × 5.3°	3.3 - 26.0	256 × 192, 12µm NETD < 35mK	\$1,999
1000m	9.2°× 6.9°	2.5 - 19.8		\$1,599
	2600m 1800m 1200m	2600m 8.7° × 7° 1800m 12.5° × 10° 7.5° × 5.7° 1200m 10.5° × 7.9° 7.0° × 5.3°	2600m 8.7° × 7° 2.6 - 20.8 1800m 12.5° × 10° 1.8 - 14.6 7.5° × 5.7° 3 - 24 1200m 10.5° × 7.9° 2.2 - 17.6 7.0° × 5.3° 3.3 - 26.0	2600m 8.7° × 7° 2.6 - 20.8 640 × 512, 12 μm 1800m 12.5° × 10° 1.8 - 14.6 NETD < 20mK 7.5° × 5.7° 3 - 24 384 × 288, 12 μm 1200m 10.5° × 7.9° 2.2 - 17.6 NETD < 20mK 7.0° × 5.3° 3.3 - 26.0 256 × 192, 12μm

Thunder 3.0



Clip-On Versatility

These thermal monoculars boast high-resolution detectors @ 640 × 512, 1920 × 1080 OLED displays, and NETD < 15 mK sensitivity, offering detection ranges up to 2600 m. With a 6-hour battery life and 1000 g shock resistance, they deliver top-tier performance in any environment.

ر ا	MODEL	RANGE	FOV	MAG	SENSOR	RRP
CER.	TQ50CL 3.0	2600m	8.8° × 7.0°	×]*	640 × 512, 12 µm NETD < 15mK	\$5,499
	TH35C 3.0	1800m	7.5° × 5.7°	×]*	384× 288, 12 µm NETD < 15mK	\$3,499

*fixed at base magnification in clip-on mode

Thunder ZOOM 2.0

THERMAL SCOPE

Dual FOV Technology

With a 2.2x to 34.6x large magnification realized by the 384 detector @20mK, TH50Z 2.0 is the perfect match for both wooded and open field areas. A F0.8 large aperture also strengthens your viewing ability of objects.

	MODEL	RANGE	FOV	MAG	SENSOR	RRP
M 2.0	TQ60Z 2.0	3000m	12.5° × 10.0°/ 7.3° × 5.9°	1.8-14.6/ 3.1 - 25.0	640 × 512, 12 μm NETD < 20mK	\$6,999
ZOOZ	TH50Z 2.0	2600m	10.5° × 7.9°/ 5.3° × 4.0°	2.2-17.4/ 4.3-34.6	384 × 288, 12 µm NETD < 20mK	\$4,999

Au Office number 0488 647 667 **Au Office Email** australia@huntsmanoptics.com















